

Mynute VHE

High efficiency open vent boiler

SEDBUK 'A' RATED

COMPACT DIMENSIONS

ENERGY EFFICIENCY
RECOMMENDED

COMPATIBLE WITH ENERGY
SAVING CONTROLS



Mynute VHE

High efficiency open vent boiler

SPECIFICATIONS	Mynute 12VHE	Mynute 15VHE	Mynute 20VHE
Central Heating			
Heat input (kW)	12	15	20
Maximum heat output @ 60/80 °C (kW)	11.74	14.60	19.68
Maximum heat output @ 30/50 °C (kW)	12.64	15.74	21.16
Min static head	1m	1m	1m
Max static head	30m	30m	30m
Min flow rate at max output	500 l/h	500l/h	500l/h
Weight			
Dry weight (kg)	25	25	29
Dimensions			
Height (mm)	600	600	740
Width (mm)	340	340	400
Depth (mm)	340	340	340
Flue Details (concentric)			
Maximum horizontal flue length (60/100mm)	7.8m	7.8m	7.8m
Maximum vertical flue length (60/100mm)	8.8m	8.8m	8.8m
Maximum horizontal flue length (80/125mm)	25m	25m	20m
Maximum vertical flue length (80/125mm)	30m	30m	30m
Flue Details (twin pipes)			
Maximum horizontal flue length (80mm/80mm)	40m/40m	40m/40m	40m/40m
Maximum vertical flue length (80mm/80mm)	40m/40m	40m/40m	40m/40m
Efficiency			
SEDBUK (%)	90.3 (A)	90.0 (A)	90.5 (A)
NOx Class	5	5	5



ENERGY SAVING CONTROLS AND OPTIONS

Description	Code
Weather compensation control	2359259
*Rear flue terminal (12kW and 15kW only)	533

Further information on these controls can be found in the Vokèra Intelligent controls brochure.

SEDBUK 'A' rated.

Reduces running costs by up to 35% more than a conventional boiler, helping to safeguard the environment.

Low pressure loss reduces noise and increases pump performance.

Low-NOx - highest class-5 performance.

Anti-cycling control reduces on/off cycling, increasing efficiency of the boiler and reducing fuel costs.

Built-in thermo-regulation to increase further fuel efficiency.

Adding a Vokèra energy saving control to the Vokèra Mynute VHE can increase the boilers efficiency by a further 10% so ask your installer about the range of Vokèra energy saving controls.

Built-in frost protection, protects the appliance from damage during periods of cold weather. External pump must be connected directly to the boiler to ensure this function operates.

Versatile, horizontal, vertical or rear flueing* options – using Vokèra's concentric or twin flue systems – enable the boiler to be sited almost anywhere in the home.

Pump anti-block eliminates the risk of pump seizure during periods of inactivity.

Compatible with Zenith Solar thermal.

Intuitive control panel ensures the appliance is easy to operate and adjust.

Can be converted to LPG with LPG kit.

Compact dimensions, with kitchen cupboard fit on Mynute 12VHE and 15VHE models.

MYNUTE VHE CONTROL PANEL



Vokèra Ltd Borderlake House, Unit 7 Riverside Industrial Estate, London Colney, AL2 1HG

Email: enquiries@vokera.co.uk Web: www.vokera.co.uk

Tel: 0844 391 0999

Fax: 0844 391 0998

Vokèra Ireland West Court, Callan, Co Kilkenny

Tel: 056 7755057

Fax: 056 7755060

Vokèra Limited reserve the right to change specification without prior notice. Consumers statutory rights are not affected. A Riello Group Company. Company Reg No.: 1047779

Vokèra is a licensed member of the Benchmark scheme which aims to improve the standards of installation and commissioning of domestic hot water systems in the UK.